



SPECIFICATION

Electric
 Current Rating: 5Amp
 Insulator Resistance: 1000M ohm Min.
 (At 500V DC)
 Dielectric Strength: 1000V For One Minute
 Temperature : -55 ° C ~+105 ° C

MATERIAL&FINISH

Shell: Insulator Glass Filled Nylon
 Stell: Zinc Plated Or Tin Plated
 Pin Contact: Brass, Gold Plated Over Nickel

Shell Size	A	B	C	D
9M	16.92	24.99	30.81	19.28
15M	24.25	33.32	39.14	27.51
25M	38.96	47.04	53.04	41.30
37M	55.42	63.50	69.32	57.71

ORDER INFORMATION

C0542 -

09
 15
 25
 37
 50

M: Male
 A: Throught Hole
 A: Non Accessories
 A: Tin+Dimple
 B: Nickel+Dimple
 Z: Zinc(Chromatic)
 B: Black
 Fill It With "0"

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

制表日: 2002/12/04
 DRAWING. APPROVED
 kevin

UNIT		SCALE	PART NAME	
MM		2:1	D-SUB CRIMPING HOUSING (MALE)	
APPD.	CKD.	TOLERANCE	PART NO.	REV.
		± 0.3	C0542-XXMAAXX0	A