



SPECIFICATION

Current Rating: 2A AC, DC
 Voltage Rating: 250V AC, DC
 Temperature Range: -25 °C ~+85 °C
 Contact Resistance: 20 m ohms Max.
 Insulation Resistance: 1,000Mohms Mn.
 Withstanding Voltage: 1,500V AC/minute.
 Material: Nylon 66, UL94V-2

Poles	Dimension	
	A	B
2	2.54	5.64
3	5.08	8.16
4	7.62	10.72
5	10.16	13.30
6	12.70	15.78
7	15.24	18.40
8	17.78	20.80
9	20.32	23.50
10	22.86	26.00
11	25.40	28.50
12	27.94	31.00
13	30.48	33.50
14	33.02	36.00
15	35.56	38.50
16	38.10	41.20
17	40.64	43.60
18	43.18	46.32
19	45.72	48.80
20	48.26	51.34

ORDER INFORMATION

H2510 -

02-20 P: Non Distribution Y: W/Locking Rib W: White Fill It With "0" Fill It With "0" Fill It With "0"

玄茂科技股份有限公司
 HSUAN MAO TECHNOLOGY CO., LTD.

UNIT

SCALE

PART NAME

MM
INCH

2:1

MX2.54mm HOUSING

APPD.

CKD.

TOLERANCE

PART NO.

REV.

制表日: 2002/12/04

DRAWING.

APPROVED

±0.3

H2510-XXPXW000

A

Jane