



SECTION: A-A'



SECTION: B-B'



SECTION: C-C'

**SPECIFICATION**

Current Rating: 13A AC/DC.

Voltage Rating: 650V AC/DC.

Contact Resistance:  $5M\Omega$  (Max)

Insulation Resistance:  $1000M\Omega$  Min.

Withstand Voltage: 1500V AC / 1 Minute.

Temperature Range:  $-25^{\circ}C$  to  $+85^{\circ}C$

Applicable Wire: AWG#14 to #22

Accepts: H6350 Series

**Contact Information**

Part No.	Wire Range	Insulation O.D.	DIM(mm)				Material	Finish	Q'ty/Reel
			A	B	C	D			
T6350-TBD00000	AWG #18-#22	2.80mm(MAX.)	3.3	3.3	2.4	2.4	Brass	Tin-plated	3500pcs/R
T6350-TBR00000	AWG #16-#20	3.00mm(MAX.)	4.5	4.4	2.9	3.5	Brass	Tin-plated	3500pcs/R
T6350-TBQ00000	AWG #12-#14	3.70mm(MAX.)	6.4	5.7	2.9	3.5	Brass	Tin-plated	2500pcs/R

**玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**

UNIT

SCALE

PART NAME

MM

4:1

6.35mm Pitch Wire to Wire  
 Female Crimp TERINNAL

制表日: 2002/12/04

DRAWING.

APPROVED

APPD.

CKD.

TOLERANCE

PART NO.

REV.

*Jane*

$\pm 0.5$

T6350-XBX00000

A