



**SPECIFICATION**  
 Current Rating: 2.5A AC, DC  
 Voltage Rating: 250V AC, DC  
 Temperature Range: -25° C ~+85° C  
 Contact Resistance: 20 m ohms Max.  
 Insulation Resistance: 1,000M ohms Min.  
 Withstanding Voltage: 1,000V AC/minute.  
 Material: Nylon 66, UL94V-0  
 Pin: Brass, Tin Plated

CIRCUIT	DIMENSION	
	A	B
2	2.50	7.50
3	5.00	10.00
4	7.50	12.50
5	10.00	15.00
6	12.50	17.50
7	15.00	20.10
8	17.50	22.60
9	20.00	25.10
10	22.50	27.60
11	25.00	30.10
12	27.50	32.60
13	30.00	35.10
14	32.50	37.60
15	35.00	40.10
16	37.50	42.60
17	40.00	45.10
18	42.50	47.60
19	45.00	50.10
20	47.50	52.60

玄茂科技股份有限公司  
 HSUAN MAO TECHNOLOGY CO.,LTD.

UNIT  
 MM  
 INCH  
 APPD. CKD.  
 TOLERANCE  
 ± 0.5

PART NAME  
 XH 2.5 WAFER 90°  
 PART NO. REV.  
 W7600-XXPRXTX0 A

製表日:2000/05/14

DWG. APPROVED  
 TINA SHELLEY

1 2 3 4 5 6 7 8